



1 After unpacking the carton, unscrew the bolts from the back housing of the speaker.



2 Take out the back cover and feed the wires from the cable line side through the glands of the cover.




Onnect the cable line wires to the ceramic block – select proper power tapping – look at the diagram. It is suggested to cut the cable insulation beforehand for easier mounting in the ceramic block (the internal wire isolation should be cut at least 7 mm). Check the stability of the connection. For more safety in wires connection, a metal sleeve shall be used to connect the two wires in the terminal.



Put on and screw the back cover of the speaker housing.



5 Fix the bracket of the loudspeaker to the wall with screws. Then regulate the position of the loudspeaker in order to optimize a sound direction.



## **SAFETY PRECAUTIONS:**

- 1. After unpacking, check the speaker and its enclosure for damage;
- 2. Read this installation manual carefully before starting installation process consider installation options from this instruction depending on the number of wires in the cable line or the line control method;
- 3. Check if fitting method (ceiling, wall, pendant etc) complies with EN 54 certificate, catalogue data or local approval if concerns;
- 4. Install the speaker only in a location that can structurally support the full weight of the unit and mounting bracket;
- 5. Do not use other methods than specified to install the speaker. Ensure that all screws are securely tightened. Do not mount the speaker in locations exposed to constant vibration.
- Not keeping higher above rules may cause the speaker could fall down, possibly resulting in personal injury;
- 6. When connecting speaker line cables check also if the power tap selected on the transformer is the correct one follow system design. Change if necessary.
- 7. Make sure amplifier's power is switched off when connecting the speakers, to avoid electric shocks.

